

## ID 970

## Single stage controller for temperature

The ID 970 controllers are devices suitable for applications on normal or low temperature refrigerating units. They are provided with a PTC thermostatic probe input (NTC can be selected by parameter) and two relay outputs for compressor and defrost management. Defrost cycles can be controlled at time intervals. The value of the probe's reading is viewed on a display by three digits and a minus sign; the decimal point reading can be set by parameter. All the versions are provided with a TTL connection in order to use Copy Card, the quick programming accessory. In addition, the 16 A compressor relay options and the buzzer are provided. These controllers are available in the 32x74 standard format and the power supply voltage is, on choice, 230 Va or 12 Va/c.

### Technical Data

<b>Frontal protection</b>	IP 65
<b>Container</b>	plastic resin PC+ABS UL94V-0
<b>Dimensions</b>	32x74 mm, depth 60 mm
<b>Mouting</b>	panel mounting, cut out 29x71 mm (+0.2/-0.1mm)
<b>Usage temperature</b>	-5...55°C
<b>Storage temperature</b>	-30...85°C
<b>Usage environment humidity</b>	10...90% RH
<b>Storage environment humidity</b>	10...90% RH
<b>Display</b>	3½ digits plus sign
<b>Precision</b>	above 0.5% of bottom scale + 1 digit
<b>Consumption</b>	3 VA
<b>Resolution</b>	1°C or 0.1°C (selectable with a parameter).
<b>Power supply</b>	230Vac, 12Vac/cc ± 15%, 50/60Hz



